



Original-Peddinghaus
Punching Machine
with Hydraulic Drive System

Hydraulic 280



42260

Technical Data

rated capacity	kN	280
stroke	mm	30
stroke adjustable	mm	10 - 30
number of strokes, 10 mm	min ⁻¹	43
working height to die	mm	1,033
fitting height	mm	223
throat depth	mm	250
width of tool support	mm	225
punches with standard punching attachment	up to mm	Ø 31 in 7
	up to mm	Ø 15 in 15
punches with oversize punching attachment SV 58	up to mm	Ø 58 in 4
	up to mm	Ø 65 in 3.5
Machine Data		
power rating	kW	3
charge of oil	l	32
net weight with oil	appr. kg	560
overall machine dimensions L x W x H	cm	73 x 54 x 153
ref. no		42260

All capacities refer to material with a tensile strength of 450 N/mm².
We reserve the right to make design alterations without notice.

Hydraulic 280

Standard scope of delivery


- quick-change punching attachment up to 31 mm Ø, for punches and dies of the **green series**
- stripper, swivable and height-adjustable, with exchangeable plate
- foot pedal and electric control elements
- integrated hydraulic power pack
- three-phase A.C. motor, 400 Volt, 50 Hz




swing-away stripper, height-adjustable

Accessories


518
Ledge table




539
Ledge table



546
Ledge table



513
Ledge table



548 Plus
Ledge table



table width: 800 mm

316
Tooling set, punches and dies

